

H3C 驱动相关信息:

CPU架构	服务器机型	网卡类别	型号	固件版本:	驱动		
					BC-Linux Euler 21.10	BC-Linux8.2(kernel:4.19.0-240.23.11.el8_2.bclinux.x86_64)	BC-Linux8.2(kernel:5.10.0-200.el8_2.bclinux.x86_64)
INTEL	R4900G3 R4300G3	网卡	NIC-ETH540F-LP-2P	14.29.1016	5.7-1.0.2.0	5.8-1.1.2.1	5.8-1.1.2.1
			NIC-620F-B2-25Gb-2P	14.29.1016	5.7-1.0.2.0	5.8-1.1.2.1	5.8-1.1.2.1
			NIC-GE-4P-360T-L3	4.10.0x80001a631.2585.0	2.21.12	2.21.12	2.21.12
			NIC-GE-4P-360T-B2	1.63.01	5.9.3	5.6.0-k(系统自带)	5.9.3
			CNA-10GE-2P-560F-B2	4040.4042	5.14.6	5.1.0-k(系统自带)	5.14.6
			NIC-BCM957302-F-B-10Gb-2P	20.8.171.0	1.10.2-222.0.142.0	1.10.2-222.0.142.0	1.10.2-222.0.142.0
			NIC-MCX512A-ACAT-F-2*25Gb	16.33.1048	5.7-1.0.2.0	5.8-1.1.2.1	5.8-1.1.2.1
		阵列卡	RAID-LSI-9361-8i	24.21.0-0148	07.720.04.00	07.720.04.00	07.720.04.00
			HBA-LSI-9440-8i	51.20.0-4342	07.720.04.00	07.720.04.00	07.720.04.00
			HBA-LSI-9311-8i	16.00.16.00	36.00.00.00	36.00.00.00	36.00.00.00
			RAID-P460-B4	5.00	2.1.16-030	1.2.10-025(系统自带)	2.1.16-030
			HBA-H460-M1	5.00	2.1.16-030	1.2.10-025(系统自带)	2.1.16-030
			HBA-H460-B1	5.00	2.1.16-030	1.2.10-025(系统自带)	2.1.16-030

CPU架构	服务器机型	网卡类别	型号	固件版本:	驱动		
					BC-Linux Euler 21.10 (kernel: 4.19.90-2107.6.0.0100.oe1.bclinux.x86_64)	BC-Linux8.2(kernel:4.19.0-240.23.11.el8_2.bclinux.x86_64)	BC-Linux8.2(kernel:5.10.0-200.el8_2.bclinux.x86_64)
AMD	R4950G5	网卡	UN-NIC-620F-B2-25Gb-2P-1	14.32.1010	5.7-1.0.2.0	5.8-1.1.2.1	5.8-1.1.2.1
			UN-NIC-ETH360T-3S-4P	1.63.01	5.10.2	5.10.2	5.10.2
		阵列卡	UN-RAID-LSI-9361-8i(2G)-1	24.21.0-0148	07.721.02.00	07.721.02.00	07.721.02.00

CPU架构	服务器机型	网卡类别	型号	固件版本:	驱动		
					BC-Linux Euler 21.10 (kernel: 4.19.90-2107.6.0.0100.oe1.bclinux.x86_64)	BC-Linux8.2(kernel:4.19.0-240.23.11.el8_2.bclinux.x86_64)	BC-Linux8.2(kernel:5.10.0-200.el8_2.bclinux.x86_64)
海光	R4930G5 R4330G5	网卡	UN-NIC-620F-B2-25Gb-2P-1	14.32.1010	5.7-1.0.2.0	5.8-1.1.2.1	5.8-1.1.2.1
			UN-NIC-ETH540F-LP-2P	14.32.1010	5.7-1.0.2.0	5.8-1.1.2.1	5.8-1.1.2.1
			UN-NIC-ETH360T-3S-4P	1.63.01	5.10.2	5.10.2	5.10.2
		阵列卡	UN-HBA-H460-B1-F	5.00	2.1.16-030	系统自带	2.1.16-030
			UN-RAID-LSI-9460-16i(4G)-F	51.20.0-4342	07.720.04.00	07.720.04.00	07.720.04.00

mlnx 驱动安装

解压 tgz 文件后

```
cd MLNX_OFED_LINUX-5.7-1.0.2.0-bclinux21.10sp2-ext
```

```
./mlnxofedinstall
```